

EXIGE

Reliable and efficient healthcare refrigeration, every time

Exige provides premium cooling technology that exceeds expectations, delivering reliable, easy-to-use and energy efficient refrigeration that laboratories and pharmacies can trust. Developed to meet rigorous requirements, Exige embodies the resilience necessary to maintain temperatures in healthcare environments.

With Exige, maintaining the integrity of products becomes effortless. Ensuring peace of mind and optimal performance.

- **Easy to use**
intuitive menu for simple training and onboarding
- **Digital display**
and flat touch keypad on electronic controller
- **Documentation**
of historical temperature compliance
- **Live temperature**
monitoring for extra control and peace of mind
- **Integrated alarms**
to ensure temperature control is fully maintained
- **Ø27mm access port**
for external temperature sensors

- **Hygienic interior**
finishing in stainless steel with pressed bottom
- **Adjustable interior**
design for grid shelving or drawers
- **Self-closing doors**
with easy-clean magnetic sealing gaskets
- **80mm thermal insulation**
with no ODP or GWP
- **Telescopic legs**
with optional swivel castors





EXIGE

Pharmaceutical & laboratorial

The Exige product range represents durability, functionality, and energy efficiency, providing pharmaceutical and laboratory professionals with a dependable and user-friendly cooling solution.

With Exige, the complexity of preserving sample collections, specimen cultures, and healthcare items is made effortless, thanks to its consistent top-tier performance and precise temperature control.

Control features include



Easy-to-use

Intuitive menu with clear designs



Complete documentation

Temperature history, temperature compliance report



Temperature control

Live temperature monitoring for extra control

EXIGE



ECSS-550 Pharma
Exige Refrigerator

ECSG-550 Pharma
Exige Refrigerator Glazed Door

Specifications

Set operating temperature	+5 °C
Temperature range	+2 °C to +8 °C
Ambient temperature range	+10 °C to +40 °C
Gradient	3 °C
Exterior dimensions (WxDxH)	720x850x2040 mm
Interior dimensions (WxDxH)	560x680x1430 mm
Gross volume / Net volume	550 L / 467 L

Technical data

Power supply	220-240 V / 50 Hz
Input power	190 W / 0,83 A
Cooling power	431 W
Refrigerant fluid	R290

Operation

Cooling system	Forced-draft
Defrost	Automatic
Electronic controller interface	Flat touch keypad with digital display
Battery (72 h back-up)	Option
Power failure alarm	When power returns
Warning signal	Visual and audible
Volt-free (dry contact)	Option

Cabinet finishing

External	304-grade stainless steel
Internal	441-grade stainless steel
Door	Stainless steel Glazed door

Connectivity

Connectivity	Option
--------------	--------

Additional features

Internal LED lighting	Yes
Interior fitting	7 medicine drawers + 3 grid shelves
Drawers material	Plastic with antibacterial coating
Usable area in mm (WxD)	500 x 570mm / 650 x 530mm
Max. load (per grid shelf)	30 kg
Max. load (per drawer)	12 kg
Castors	Option
Lock	Yes
Access port	1 x Ø 27 mm
Door hinges	Right hinges (reversible)



ECWS-550 Pharma
Exige Refrigerator White

ECWG-550 Pharma
Exige Refrigerator White Glazed Door

Specifications

Set operating temperature	+5 °C
Temperature range	+2 °C to +8 °C
Ambient temperature range	+10 °C to +40 °C
Gradient	3 °C
Exterior dimensions (WxDxH)	720x850x2040 mm
Interior dimensions (WxDxH)	560x680x1430 mm
Gross volume / Net volume	550 L / 467 L

Technical data

Power supply	220-240 V / 50 Hz
Input power	190 W / 0,83 A
Cooling power	431 W
Refrigerant fluid	R290

Operation

Cooling system	Forced-draft
Defrost	Automatic
Electronic controller interface	Flat touch keypad with digital display
Battery (72 h back-up)	Option
Power failure alarm	When power returns
Warning signal	Visual and audible
Volt-free (dry contact)	Option

Cabinet finishing

External	White galvanized steel
Internal	441-grade stainless steel
Door	White Glazed door

Connectivity

Connectivity	Option
--------------	--------

Additional features

Internal LED lighting	Yes
Interior fitting	7 medicine drawers + 3 grid shelves
Drawers material	Plastic with antibacterial coating
Usable area in mm (WxD)	500 x 570 mm / 650 x 530 mm
Max. load (per grid shelf)	30 kg
Max. load (per drawer)	12 kg
Castors	Option
Lock	Yes
Access port	1 x Ø 27 mm
Door hinges	Right hinges (reversible)

Pharmaceutical refrigeration

Pharmaceutical refrigeration