



Top Class Products & Services nv
Wingepark 16a
B-3110 ROTSELAAR
BELGIUM

Lab equipment and more

sales@tcps.be
T:016/53.71.30

Data Sheet for type SR (Laboratory and Transfer Sterilizers):

Model / Type		SR 53	SR 115	SR 240	SRW 400	SRW 750	SRW 1000
Air convection		Natural (SRN) / forced (SR)			Forced		
Chamber capacity (l)		56	112	245	424	749	1005
Usable volume of the chamber (l)		56	112	245	424	749	1005
Door type		Solid / door with viewing window (option)					
Temperature range (°C)		5°C above ambient temperature ...+ 250°C					
Temperature resolution (°C)		Every 0,1					
Controller		4,3" inch color touch panel					
Display		Microprocessor PID with a graphical LCD display					
Interior		Acid-proof stainless steel to DIN 1.4301					
Housing	SMART	Power coated sheet					
	IG SMART	Stainless steel linen finish					
Overall dims (mm)	A Width	590	650	810	1010	1260	1260
	B Height	700	850	1200	1430	1600	2000
	C Depth	620	710	770	780	870	880
Internal dims (mm)	D Width	400	460	600	800	1040	1040
	E Height	390	540	800	1040	1200	1610
	F Depth	360	450	510	510	600	600
Max shelf workload (kg)	-	25	25	25	25	-	-
	Reinforced version	50	50	100	100	100	100
Max unit workload (kg)	-	40	60	90	120	140	-
	Reinforced version	-	-	-	-	-	-
Nominal power (W)		1700	2500	3100	4000	5500	5500
Weight (kg)		50	65	126	174	260	330
Temperature protection		Class 2.0 to DIN 12880 (Class 3.1 option)					
Power supply		230 V 50 Hz			400 3/N		
Shelves fitted/max		2/5	2/7	3/10	3/14	5/16	6/22